

APPLICABLE STANDARD		SPECIFICATIONS				
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾		
	VOLTAGE	100 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %		
	CURRENT	0.5 A	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾		
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
MARKING	CONFIRMED VISUALLY.				<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).		40 mΩ MAX.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)		50 mΩ MAX.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
MILLIVOLT LEVEL METHOD						
INSULATION RESISTANCE	250 V DC		100 MΩ MIN.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
VOLTAGE PROOF	300 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
MECHANICAL CHARACTERISTICS						
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
VIBRATION	FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.5 mm, AT 2 h FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
SHOCK	490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				<input checked="" type="checkbox"/> <input type="checkbox"/>	
ENVIRONMENTAL CHARACTERISTICS						
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.		① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE-55→+15~+35→ +85→+15~+35°C TIME 30 → MAX 5 → 30 → MAX 5 min UNDER 5 CYCLES.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)				<input checked="" type="checkbox"/> <input type="checkbox"/>	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
	2) SOLDERING IRONS : 360 °C, FOR 5 s				<input checked="" type="checkbox"/> <input type="checkbox"/>	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 240±3°C, FOR IMMERSION DURATION, 3 s.		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.		<input checked="" type="checkbox"/> <input type="checkbox"/>	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
						
REMARK ⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. Unless otherwise specified, refer to MIL-STD-1344.				APPROVED	HS. OKAWA	08. 07. 23
				CHECKED	HT. YAMAGUCHI	08. 07. 23
				DESIGNED	SY. KAMIGA	08. 07. 22
				DRAWN	HK. SUNADORI	08. 07. 17
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-084966-23	
	SPECIFICATION SHEET			PART NO.	FX6-40P-0.8SV1 (93)	
	HIROSE ELECTRIC CO., LTD.			CODE NO.	CL576-0023-6-93	 1/1