

REV. B

DCO 300860

TOLERANCES $\pm .010"$ - UNLESS
OTHERWISE SPECIFIED


COIL: @ 25°C	320 OHMS $\pm 10\%$
RESISTANCE	28 VDC
NOMINAL VOLTAGE	13.5 VDC MAX.
MUST OPERATE	
MUST RELEASE	5.5 VDC MAX., 2.3 VDC MIN.

ENVIRONMENT:

VIBRATION	10	Hz	TO	3000	Hz	0	30	g's
SHOCK	200	g's	6	MS.	DURATION			
TEMPERATURE	-70	°C	TO	+125	°C			
NOTES: OPERATE, RELEASE 10 MS MAX.								
CONTACT BOUNCE 1 MS MAX.								

CUSTOMER DATA SHEET

A1 O — X2 O — A2 O A3



BLUE BEAD
TERMINAL VIEW

CONTACT RATING:
25 AMPS 28 VDC, 115 VAC 400 Hz RESISTIVE
50,000 OPERATIONS

DR. B.D. 21MAY2008 CK. J.M.B. 5/21/08

 ©COPYRIGHT 2005
TYCO ELECTRONICS CORPORATION
ALL INTERNATIONAL RIGHTS RESERVED

CUST. QPL
CUST. NO. M6106/19-011 REV. ----

TE NUMBER
1-1617748-7

CII PART NUMBER

FC A-125-11

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[FCA-125-11](#)