



RoHS Compliant

REVISIONS							
Rev	DESCRIPTION	DATE	DRAWER	Rev	DESCRIPTION	DATE	DRAWER
A	Initial Drawing	2019.09.03	Jane Shen	C			
B				D			
SPECIFICATIONS							
RATING		DC12V 50mA		TIMING			
CONTACT RESISTANCE		100mΩ MAX.		OPERATION (TORQUE)			
INSULATION RESISTANCE		DC500V – 100MΩ MIN.		STROKE (ANGLE)		0.15±0.1 mm	
WITHSTAND VOLTAGE		AC250V – 1 MINUTE		LIFE		CYCLES	
REMARKS:		Waterproof Grade : IP67					



→ → →

Model No.	H	OPERATING FORCE	LIFE
NTC203-AT1J-A160T	4.3	160±50 gf	50,000
NTC203-AT1J-B160T	5.0		
NTC203-AT1J-A260T	4.3	260±70 gf	30,000
NTC203-AT1J-B260T	5.0		

TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.1		SIGNATURES	DATE	MODEL
		DRAWER Jane Shen	2019.09.03	TITLE TACT SWITCH
		CHECKED		
		REVIEWED		NO.
		APPROVALS		See Model No.

TAIWAN MISAKI ELECTRONICS CO., LTD.

Qinyuan Chuang 2019.09.03
Jianying Shu 2019.09.03

Sandry Su

Qiu Yuan Chuang

7	TAPE	1	POLYIMIDE	
6	CONT. T PLATE	1	STAINLESS STEEL PLATE	Ag PLATING
5	TERMINAL	4	COPPER ALLOY	Ag PLATING OVER Ni PLATING
4	NOUMENON COVER	1	LIQUID CRYSTAL POLYMER	BLACK COLOR
3	FRAME	1	POLYAMIDE RESIN	BLACK COLOR
2	STEM	1	LIQUID CRYSTAL POLYMER	COLOR □160:BLACK, □260:NATURAL
1	COVER	1	STAINLESS STEEL PLATE	
NO.	PART NAME	Q'TY	MATERIAL	SPECIFICATION

				SIGNATURES	DATE	M O D E L
				DRAWN Jane Shen	2019.09.03	TITLE
				CHK'D		TACT SWITCH
				REV'D		NO.
				APP'D		NTC203-AT1J-A 260T
SYM	DESCRIPTION	DATE	APPROVED			DWG NO.
TAIWAN MISAKI ELECTRONICS CO.,LTD.						TC203-02

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant

Model: NTC203-AT1J Series

1. Test condition:

Standard test conditions shall be 5~35°C in temperature, 45~85%RH in humidity and 86~106Kpa in atmospheric pressure. Should any doubt arise in judgment, tests shall be conducted at 20±2°C in temperature, 60~70% RH in Humidity and 86~106 kpa in atmospheric pressure.

2. Operating temperature range: -40 ~ +85°C

Storage temperature range: -40 ~ +85°C


3. Construction:

3.1 Shape and dimension are subject to attached drawing regulation.

3.2 Appearance: Whole should be a good completion, no rust, no crack and good plating.

4. Rating: 12V D.C. , 50mA.

5. Electrical Performance:

No.	Items	Test conditions	Specifications
5.1	Contact Resistance	Shall be measure at 1kHz±200Hz (MAX. 20mV, MAX. 50mA.) or 1 A, 5V D.C. By voltage drop method.	100mΩ Max.
5.2	Insulation Resistance	Shall be measured by applying 500V D.C. Between all terminals and between the terminals and the frame for 1 minute ± 5 seconds.	100 MΩ Min.
5.3	Withstand Voltage	250V A.C. (50~60Hz 2mA) shall be applied between all terminals and between the terminals and the frame for 1 minute.	No dielectric breakdown shall be occurred.
5.4	Bounce	Lightly striking the center of the stem at a rate encountered in normal use (3 to 4 operations per sec.) 	ON: 10m sec Max. OFF: 10m sec Max.

APPROVED BY

REVIEWED BY

CHECKED BY

DESIGNED BY

SPEC NO.

Qiuyuan Chuang

Jane shen
2018.09.10

SE-TC101N
PAGINATE

A NEW RELEASE

SYM DISRIPTION



DATE

1/5

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant



6. Mechanical Performance:

No.	Items	Test conditions	Specifications
6.1	Operating Force	Placing the switch such that the direction of switch operation is vertical and then gradually increasing the load applied to the center of the stem, the maximum load required for the switch to come to a stop shall be measured. 	Push force: $160 \pm 50\text{gf}$ $260 \pm 70\text{gf}$ Return force: 20 gf min.
6.2	Travel	Placing the switch such that the direction of switch operation is vertical and then applying a below static load to the center of the stem, the travel distance for the switch to come to a stop shall be measured.  	$0.15 \pm 0.1 \text{ mm.}$

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
						Jane shen	SE-TC101N
						2018.09.10	PAGINATE
A	NEW RELEASE						2/5
SYM	DISCRIPTION	DATE					

SPECIFICATIONS FOR TACT SWITCH


RoHS Compliant

No.	Items	Test conditions	Specifications										
6.3	Push Strength	Placing the switch such that the direction of switch operation is vertical and then a below station load shall be applied in the direction of stem operation. 3kgf for 15seconds 	No damage. (Electrical and mechanical)										
6.4	Solderability	Test Temperature : 235 ± 5°C Immersion Angle : 90° Immersion Speed : 1 mm/sec. Immersion Depth : 0.1mm Dwell Time : 5 seconds  <table><tr><th>Para.</th><th>Criteria</th></tr><tr><td>Tb</td><td>≤ 1 second</td></tr><tr><td>F1</td><td>50% of maximum theoretical wetting force at or before two seconds</td></tr><tr><td>F2</td><td>No less than 90% of the F1 Value</td></tr><tr><td>AA</td><td>Area calculated using sample buoyancy and 50% maximum theoretical force</td></tr></table>	Para.	Criteria	Tb	≤ 1 second	F1	50% of maximum theoretical wetting force at or before two seconds	F2	No less than 90% of the F1 Value	AA	Area calculated using sample buoyancy and 50% maximum theoretical force	Conform to the criteria in the left table.
Para.	Criteria												
Tb	≤ 1 second												
F1	50% of maximum theoretical wetting force at or before two seconds												
F2	No less than 90% of the F1 Value												
AA	Area calculated using sample buoyancy and 50% maximum theoretical force												

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
						Jane shen	SE-TC101N
						2018.09.10	PAGINATE
A	NEW RELEASE		Quiyuan Chuang				
SYM	DISCRIPTION	DATE					3/5

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant

No.	Items	Test conditions	Specifications
6.5	Solder Heat Resistance	(1) Manual soldering temperature: Temperature: 350°C Max. Time: 3 Sec. Max. (2) Reflow Soldering: Number of reflow pass: 2 cycles. 	Shall be free from pronounced deforming in appearance. Item 5.1~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied.


7. Weather Performance:

No.	Items	Test conditions	Specifications
7.1	Humidity Test	(1) Temperature: 60±2°C. (2) Relative humidity: 90~95% (3) Duration of test: 500 Hour. (4) Take off drop water. (5) Standard conditions after test: 1 Hour.	Contact resistance: 500mΩ Max Item 5.2~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied.
7.2	Heat Test	(1) Temperature: 85±2°C. (2) Duration of test: 500 Hour. (3) Standard conditions after test: 1 Hour.	
7.3	Cold Test	(1) Temperature: -40±2°C. (2) Duration of test: 500 Hour. (3) Take off drop water. (4) Standard conditions after test: 1 Hour.	

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
			Qinyuan Chuang			Jane shen	SE-TC101N
						2018.09.10	PAGINATE
A	NEW RELEASE						
SYM	DISCRIPTION	DATE					4/5

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant

7.4	Waterproof test	Immersion tank water-level on enclosure: 0.15 M above top. 1 M above bottom. Duration of test : 30 min.	Contact resistance: 500mΩ Max Item 5.2~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied.
7.5	Temperature cycle	(1) Test cycle: 20 cycles. (2) Standard conditions after test: 1 Hour.  A: +85±2°C B: -40±2°C C: 2 hour D: 1 hour E: 2 hour F: 1 hour	Contact resistance: 500mΩ Max Item 5.2~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied.

8. Durability:


No.	Items	Test conditions	Specifications
8.1	Life Test	(1) 5V D.C. , 5mA Resistance load. (2) Operating speed:120 cycles/minute. (2) Push force: Maximum value of operation force. (3) Operation number: 160gf=50,000 times. 260gf=30,000 times.	Contact Resistance: 2Ω MAX. Bounce: 20m sec Max.(ON,OFF) Operating Force: Within ±30% of specifications. Item 5.2 shall be satisfied. Item 6.2 shall be satisfied.

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
						Jane shen	SE-TC101N
						2018.09.10	PAGINATE
A	NEW RELEASE		Qiuyuan Chuang				
SYM	DISCRIPTION	DATE					5/5

THE PACKING SPECIFICATIONS

RoHS Compliant


1.STRUCTURE AND MATERIALS



③	COVER TAPE	POLYESTER
②	CARRIER TAPE	POLYSTYRENE
①	REEL	POLYSTYRENE
NO.	PARTS NAME	MATERIALS


- PACKAGING QUANTITY : 1,800 PCS/REEL
- MORE THAN 10 EMPTY POCKETS SHOULD BE REMAINED AT BOTH ENDS OF THE CARRIER TAPE FOR EACH REEL.
- SHORTAGE LESS THAN 10 PCS A REEL IS ACCETABLE BUT MORE THAN 3 RUNNING POCKETS SHORTAGE IS NOT ALLOWED.
- STRIPPING STRENGTH OF COVER TAPE IS BETWEEN 10 gf TO 130 gf AND STRIPPING ANGLE SHOULD BE WITHIN 165° ~ 180 °.
- THE PRODUCT IN THE POCKET OF CARRIER TAPE SHOULD BE PLACED IN A SPECIFIED CORRECT POSITION.
- TAPE AND REEL PER EIA-481.
- DIMENSIONS :

CARRIER TAPE




DRAWING DIRECTION

COVER TAPE



REEL



				APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	MODEL NO.
							Jane Shen	NTC203-AT1J-A
								PAGINATE.
								1/1
								SPEC NO.
								P-113
SYM	DISCRIPTION	DATE	APPROVED					

TAIWAN MISAKI ELECTRONICS CO.,LTD.