





REV.	ECN NO.	DESCRIPTION	DRAW	APPD.	DATE
---	---	新版本发行			2024.10.10

- NOTES:
- SPECIFICATION:
- CURRENT RATING: 5.0A MAX
 - VOLTAGE: 100 VAC
 - TEMPERATURE RANGE: -30 °C ~ 85 °C
 - CONTACT RESISTANCE: 40 MILLIONHM MAX
 - INSULATION RESISTANCE: 100 MEGOHMS MIN.
 - INSERTION FORCE: 5N~20N
 - UNMATING FORCE: 8N~20N
 - DURABILITY: 10,000 CYCLES



PIN	SIGNAL NAME	PIN	SIGNAL NAME
A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DM1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
7	COVER SHELL	STAINLESS STEEL	NI Plated	1PCS
5	SHIELDING PLATE	STAINLESS STEEL	NI Plated	1PCS
4	MD	HIGH TEMPERATURE PLASTIC	BLACK	1PCS
3	CONTACT	COPPER ALLOY	Au/Ni, TIN Plated	1SET
2	CONTACT	COPPER ALLOY	Au/Ni, TIN Plated	1SET
2	HOUSING	HIGH TEMPERATURE PLASTIC	BLACK	1PCS

TOLERANCE	NAME(INTENDED USE)	TITLE:
X.X ±0.30 X.X' ± 2'	PART NO.	USB C F 单排10P 板 L6.5
.XX ±0.20 .X' ± 1'	AA0B011-017E	
.XXX ±0.10 .XX' ±0.5'		
UNITS	mm	
MATERILA	CHED:	
PIN	DRAW:	

SCALE	SHEET	REV.
1:1	1/2	A