KAMAYA OHM

No.:	RGC-K-HTS-0001 /13
Date:	2017. 4. 21

Data sheet

Title: FIXED THICK FILM CHIP RESISTORS; RECTANGULAR TYPE & PRECISION

Style: RGC1/32,1/20,1/16S,1/16,1/10,1/8

AEC-Q200 qualified (Without RGC1/32)

RoHS COMPLIANCE ITEM
Halogen and Antimony Free

Note: ・Stock conditions
Temperature: +5°C ~ +35°C
Relative humidity: 25% ~ 75%
The period of guarantee: Within 2 year from shipmen t by the company.
Solderability shall be satisfied.
・Product specification contained in this data sheet
are subject to change at any time without notice.
・If you have any questions or a Purchasing Specification for any quality
Agreement is necessary, please contact our sales staff.

釜屋電機株式會社
KAMAYA ELECTRIC CO., LTD.
Hokkaido Research Center
Approval by: T. Sannomiya
Drawing by: M. Shibuya

1. Scope

1.1 This data sheet covers the detail requirements for fixed thick film chip resistors; rectangular type & precision, style of RGC1/32,1/20,1/16S,1/16,1/10,1/8.

1.2 Applicable documents

JIS C 5201–1: 2011, JIS C 5201–8: 2014, JIS C 5201–8–1: 2014
IEC60115–1: 2008, IEC60115–8: 2009, IEC60115–8–1: 2014
EIAJ RC–2134C–2010

2. Classification

Type designation shall be the following form.

(Example)

RGC	1/8	C	123	D	TP
1	2	3	4	5	6
Style					

1 Fixed thick film chip resistors; rectangular type & precision — Style
2 Rated dissipation and / or dimension
3 Temperature coefficient of resistance

K	$\pm 100 \times 10^{-6}$/ °C
C	$\pm 50 \times 10^{-6}$/ °C

4 Rated resistance

123	E24 Series, 3 digit, Ex. 123--> 12kΩ,
1000	E96 Series, 4 digit, Ex. 1000-->100Ω 1022--> 10.2kΩ

5 Tolerance on rated resistance

B	±0.1%
D	±0.5%
F	±1%

6 Packaging form

B	Bulk (loose package)
PA	Press pocket taping
TH	Paper taping
TP	

3. Rating

3.1 The ratings shall be in accordance with Table–1.

Table–1

Style	Rated dissipation (W)	Temperature coefficient of resistance (10^{-6} / °C)		Rated resistance range(Ω)	Preferred number series for resistors	Tolerance on rated resistance
RGC1/32	0.03	C	± 50	100~100k	E24,96	D(±0.5%)
RGC1/20	0.05	C	± 50	1k~1M	E24,96	B(±0.1%), D(±0.5%)
		K	±100	51~976		
RGC1/16S	0.063	C	± 50	100~1M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
		K	±100	1.02M~3.3M		
				10~97.6		
RGC1/16	0.1	C	± 50	100~1M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
		K	±100	1.02M~3.3M		
				10~97.6		
				3.3~9.76		D(±0.5%)F(±1%)
RGC1/10	0.125	C	± 50	10~3.3M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
				3.3~9.76		D(±0.5%)F(±1%)
RGC1/8	0.25	C	± 50	10~4.7M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
				3.3~9.76		F(±1%)

Style	Limiting element voltage (V)	Isolation voltage (V)	Category temperature range(°C)
RGC1/32	15	50	–55~+125
RGC1/20	25		–55~+155
RGC1/16S	50	100	
RGC1/16			
RGC1/10	150		
RGC1/8	200		

3.2 Climatic category

3.2.1 RGC1/32

55/125/56

Lower category temperature	– 55 °C
Upper category temperature	+125 °C
Duration of the damp heat, steady state test	56days

3.2.2 RGC1/20,1/16S,1/16,1/10,1/8

55/155/56

Lower category temperature	– 55 °C
Upper category temperature	+155 °C
Duration of the damp heat, steady state test	56days

3.3 Stability class

5%

Limits for change of resistance:

– for long - term tests	±(5%+0.1Ω)
– for short - term tests	±(1%+0.05Ω)



Unit: mm
:Copper clad
:Solder resist

Style	a	b	c	d
RGC1/20	0.3	1.1	0.45	2.15
RGC1/16S	0.6	1.9	0.7	2.0
RGC1/16	1.0	3.6	1.2	3.0
RGC1/10	1.2	4.0	1.65	3.0
RGC1/8	2.5	5.0	2.0	2.5

RGC BOUND STRENGTH OF THE END FACE PLATING TEST SUBSTRATE



Unit: mm
:Copper clad
:Solder resist



RGC1/32 BOUND STRENGTH OF THE END FACE PLATING TEST SUBSTRATE

Figure–4

Remark 1). Material: Epoxide woven glass
Thickness: 1.6mm Thickness of copper clad: 0.035mm

• RGC1/16S,1/16,1/10,1/8



•RGC1/32,1/20



Figure–5

9. Taping

9.1 Applicable documents JIS C 0806–3: 2014, EIAJ ET–7200C: 2010

9.2 Taping dimensions

9.2.1 Press pocket taping (Paper taping, 8mm width, 2mm pitches)

Taping dimensions shall be in accordance with Figure–6 and Table–5.

Unit: mm



Figure–6

Table–5 Unit: mm

Style	A	B	t_1	t_2	t_3
RGC1/32	0.24±0.03	0.45±0.03	0.31±0.03	0.36±0.03	0.15±0.02
RGC1/20	0.37±0.05	0.67±0.05	0.42±0.03	0.45±0.05	0.27±0.02

9.2.2 Paper taping (8mm width, 2mm pitches)

Taping dimensions shall be in accordance with Figure–7 and Table–6.

Unit: mm



Figure–7

Table–6 Unit: mm

Style	A	B	t_1	t_2
RGC1/16S	$0.65^{+0.05}_{-0.10}$	$1.15^{+0.05}_{-0.10}$	0.4 ± 0.05	0.5max.

9.2.3 Paper taping (8mm width, 4mm pitches)

Taping dimensions shall be in accordance with Figure–8 and Table–7.

Unit: mm



Figure–8

Table–7 Unit: mm

Style	A	B	t_1	t_2
RGC1/16	1.15 ± 0.15	1.9 ± 0.2	0.6 ± 0.1	0.8max.
RGC1/10	1.65 ± 0.15	2.5 ± 0.2	0.8 ± 0.1	1.0max.
RGC1/8	2.00 ± 0.15	3.6 ± 0.2		

1). The cover tapes shall not cover the sprocket holes.
2). Tapes in adjacent layers shall not stick together in the packing.
3). Components shall not stick to the carrier tape or to the cover tape.
4). Pitch tolerance over any 10 pitches ±0.2mm.
5). The peel strength of the top cover tape shall be with in 0.1N to 0.5N on the test method as shown in the following RGC1/32,1/20: Figure–9, RGC1/16S, 1/16, 1/10, 1/8: Figure–10.
6). When the tape is bent with the minimum radius for 25 mm, the tape shall not be damaged and the components shall maintain their position and orientation in the tape.
7). In no case shall there be two or more consecutive components missing.
The maximum number of missing components shall be one or 0.1%, whichever is greater.
8). The resistors shall be faced to upward at the over coating side in the carrier cavity.



Figure–9



Figure–10

9.3 Reel dimension

Reel dimensions shall be in accordance with the following Figure–11 and Table–8.

Plastic reel (Based on EIAJ ET–7200C) Unit: mm



Figure–11

Table–8 Unit: mm

Style	A	B	Note
RGC1/32,1/20,1/16S,1/16,1/10,1/8	9 +1.0 0	11.4±1.0	Injection molding
		13±1.0	Vacuum forming

Note: Marking label shall be marked on a place of Marking A or two place of marking A and B.

9.4 Leader and trailer tape.

(Example)



Figure–12

10. Marking on package

The label of a minimum package shall be legibly marked with follows.

10.1 Marking A

(1) Classification

(Style, Temperature coefficient of resistance, Rated resistance, Tolerance on rated resistance, Packaging form)

(2) Quantity (3) Lot number (4) Manufacturer's name or trade mark (5) Others

10.2 Marking B (KAMAYA control label)