





RoHS Compliant




MODEL NO.	OPERATING FORCE	STROKE
NTC316-AC1T-A160T	160±50gf	0.25±0.1mm
NTC316-AC1T-A220T	220±50gf	0.3 ^{+0.1} _{-0.2} mm




REVISIONS							
Rev	DESCRIPTION	DATE	DRAWER	Rev	DESCRIPTION	DATE	DRAWER
A	Initial Drawing	2012.12.20	Jane Shen	C	Change Drawing	2013.12.19	Jane Shen
B	Change Drawing	2013.02.26	Jane Shen	D			
SPECIFICATIONS							
RATING	DC12V 50mA	TIMING					
CONTACT RESISTANCE	100mΩ MAX.	OPERATION (TORQUE)					
INSULATION RESISTANCE	DC500V-100MΩ MIN.	STROKE (ANGLE)					
WITHSTAND VOLTAGE	AC250V- MINUTE	CONTACT RESISTANCE	1Ω MAX.				
REMARKS:		(AFTER 100,000 CYCLES LIFE TEST)					

SCHEMATIC



P.C.B. MOUNTING PLAN




HATCHED AREA SHOWS SOLDERING LAND

TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.1			SIGNATURES	DATE	MODEL
DRAWER	Jane Shen	2013.12.19	TITLE	TACT SWITCH	NO.
CHECKED	Jamie Li	2013.12.19			
DRAWER	UNIT	SCALE	REVIEWED	Dennis Hung	See Model No.
	mm	10/1	APPROVALS		

TAIWAN MISAKI ELECTRONICS CO., LTD.

RoHS Compliant



NO.	PART NAME	Q'TY	MATERIAL		SPECIFICATION		
6	TAPE	1	POLYIMIDE				
5	CONTACT PLATE	1	STAINLESS STEEL PLATE		Ag-PLATING		
4	TERMINAL	4	COPPER ALLOY		Ag PLATING OVER Ni PLATING		
3	FRAME	1	POLYAMIDE RESIN		BLACK COLOR		
2	STEM	1	POLYAMIDE RESIN		<input checked="" type="checkbox"/> 160/NATURE, <input type="checkbox"/> 220/BLACK COLOR		
1	COVER	1	STAINLESS STEEL PLATE				
SYM	DESCRIPTION	DATE	APPROVED	SIGNATURES	DATE	M O D E L	
				DRAWN <i>Jane Shen</i>	2012.12.20	TITLE	TACT SWITCH
				CHK'D <i>Jamie Li</i>	2012.12.20		
				REV'D		NO.	NTC316-AC1T-A160T
				APP'D <i>Dennis Hung</i>	2012.12.21		
						DWG NO.	TC316-10
TAIWAN MISAKI ELECTRONICS CO.,LTD.							

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant

Model: NTC316-Series

1. Test condition:

Standard test conditions shall be 5~35°C in temperature, 45~85%RH in humidity and 86~106Kpa in atmospheric pressure.

Should any doubt arise in judgment, tests shall be conducted at 20±2°C in temperature, 60~70% RH in Humidity and 86~106 kpa in atmospheric pressure.

2. Operating temperature range: -40 ~ +85°C

Preservative temperature range: -40 ~ +85°C

3. Construction:

3.1 Shape and dimension are subject to attached drawing regulation.

3.2 Appearance: Whole should be a good completion, no rust, no crack and good plating.

4. Rating: 12V D.C. , 50mA.



5. Electrical Performance:

No.	Items	Test conditions	Specifications
5.1	Contact Resistance	Shall be measure at 1kHz±200Hz (MAX. 20mV, MAX. 50mA.) or 1 A, 5V D.C. By voltage drop method.	100mΩ Max.
5.2	Insulation Resistance	Shall be measured by applying 500V D.C. Between all terminals and between the terminals and the frame for 1 minute ± 5 seconds.	100 MΩ Min.
5.3	Withstand Voltage	250V A.C. (50~60Hz 2mA) shall be applied between all terminals and between the terminals and the frame for 1 minute.	No dielectric breakdown shall be occurred.



			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
			<i>Dennis Hung</i>				SE-TC20N
			2011.08.04		2011.08.04	2011.07.21	PAGINATE
A	NEW RELEASE						
SYM	DISCRIPTION	DATE					1/5

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant

No.	Items	Test conditions	Specifications
5.4	Bounce	<p>Lightly striking the center of the stem at a rate Encountered in normal use (3 to 4 operations per sec.)</p> <p>Switch</p>  <p>"ON"  "OFF" </p>	<p>ON: 10m sec Max. OFF:10m sec Max.</p>



6. Mechanical Performance:

No.	Items	Test conditions	Specifications
6.1	Operating Force	<p>Placing the switch such that the direction of switch operation is vertical and then gradually increasing the load applied to the center of the stem the maximum load required for the switch to come to a stop shall be measured.</p>  	<p>Push force: 160 +/-50 gf 220 +/-50 gf 260 +/-50 gf</p> <p>Return force: 160 gf : 20 gf min. 220&260 gf : 30 gf min</p>

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
			<i>Dennis Hung</i> 2011.08.04		Jamie Li 2011.08.04	Jane Shen 2011.07.21	SE-TC20N
A	NEW RELEASE						PAGINATE
SYM	DISCRIPTION	DATE					2/5

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant

No.	Items	Test conditions	Specifications
6.2	Travel	<p>Placing the switch such that the direction of switch operation is vertical and then applying a below static load to the center of the stem, the travel distance for the switch to come to a stop shall be measured.</p>  <p>160 gf: 0.25 +/-0.1 mm. 220 gf: 0.3 +0.1/-0.2 mm. 260 gf: 0.3 +0.1/-0.2 mm.</p>	
6.3	Push Strength	<p>Placing the switch such that the direction of switch operation is vertical and then a below station load shall be applied in the direction of stem operation.</p> <p>3kgf for 15 seconds.</p>  <p>The terminals must not fall off and no structure is damaged. Item 5.1~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied</p>	

		APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
						SE-TC20N
						PAGINATE
A	NEW RELEASE					
SYM	DISCRIPTION	2011.08.04		2011.08.04	2011.07.21	3/5

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant


No.	Items	Test conditions	Specifications										
6.4	Solderability	<p>Test Temperature : $235 \pm 5^\circ\text{C}$ Immersion Angle : 90° Immersion Speed : 1 mm/sec. Immersion Depth : 0.1mm Dwell Time : 5 seconds</p> <table border="1"> <thead> <tr> <th>Para.</th><th>Criteria</th></tr> </thead> <tbody> <tr> <td>Tb</td><td>≤ 1 second</td></tr> <tr> <td>F1</td><td>50% of maximum theoretical wetting force at or before two seconds</td></tr> <tr> <td>F2</td><td>No less than 90% of the F1 Value</td></tr> <tr> <td>AA</td><td>Area calculated using sample buoyancy and 50% maximum theoretical force</td></tr> </tbody> </table>	Para.	Criteria	Tb	≤ 1 second	F1	50% of maximum theoretical wetting force at or before two seconds	F2	No less than 90% of the F1 Value	AA	Area calculated using sample buoyancy and 50% maximum theoretical force	Conform to the criteria in the left table.
Para.	Criteria												
Tb	≤ 1 second												
F1	50% of maximum theoretical wetting force at or before two seconds												
F2	No less than 90% of the F1 Value												
AA	Area calculated using sample buoyancy and 50% maximum theoretical force												
6.5	Solder Heat Resistance	<p>(1) Manual soldering temperature: Temperature: 350°C Max. Time: 3 Sec. Max. (2) Reflow Soldering: Number of reflow pass: 2 cycles.</p>	Shall be free from pronounced deforming in appearance. Item 5.1~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied.										

		APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
		Dennis Hung				SE-TC20N
						PAGINATE
A	NEW RELEASE					
SYM	DISCRIPTION	2011.08.04		Jamie Li 2011.08.04	Jane Shen 2011.07.21	4/5

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliant

7. Weather Performance:

No.	Items	Test conditions	Specifications
7.1	Humidity Test	(1) Temperature: $60\pm2^{\circ}\text{C}$. (2) Relative humidity: 90~95% (3) Duration of test: 500 Hour. (4) Take off drop water. (5) Standard conditions after test: 1 Hour.	Contact resistance: 500mΩ Max Item 5.2~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied.
7.2	Heat Test	(1) Temperature: $85\pm2^{\circ}\text{C}$. (2) Duration of test: 500 Hour. (3) Standard conditions after test: 1 Hour.	
7.3	Cold Test	(1) Temperature: $-40\pm2^{\circ}\text{C}$. (2) Duration of test: 500 Hour. (3) Take off drop water. (4) Standard conditions after test: 1 Hour.	Contact resistance: 500mΩ Max Item 5.2~5.4 shall be satisfied. Item 6.1~6.2 shall be satisfied.
7.4	Temperature cycle	(1) Test cycle: 20 cycles. (2) Standard conditions after test: 1 Hour.	 <p> A: $+85\pm2^{\circ}\text{C}$ B: $-40\pm2^{\circ}\text{C}$ C: 2 hour D: 1 hour E: 2 hour F: 1 hour </p>

8. Durability:


No.	Items	Test conditions	Specifications
8.1	Life Test	(1) 5V D.C. , 5mA Resistance load. (2) Operating speed: 120 cycles/minute. (2) Push force: Maximum value of operation force. (3) Operation number: 100,000 times.	<p>Contact Resistance: 1Ω MAX.</p> <p>Bounce: 20m sec Max.(ON,OFF)</p> <p>Operating Force: Within $\pm30\%$ of specifications. Item 5.2 shall be satisfied. Item 6.2 shall be satisfied.</p>

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
			Dennis Hung		Jamie Li	Jane Shen	SE-TC20N
			2011.08.04		2011.08.04	2011.07.21	PAGINATE
A	NEW RELEASE						
SYM	DISCRIPTION	DATE					5/5

THE PACKING SPECIFICATIONS

RoHS Compliant

1. STRUCTURE AND MATERIALS



NO.	PARTS NAME	MATERIALS
(3)	COVER TAPE	POLYESTER
(2)	CARRIER TAPE	POLYSTYRENE
(1)	REEL	POLYSTYRENE

2. PACKAGING QUANTITY : 2,000 PCS/REEL

3. MORE THAN 10 EMPTY POCKETS SHOULD BE REMAINED AT BOTH ENDS OF THE CARRIER TAPE FOR EACH REEL.


4. SHORTAGE LESS THAN 10 PCS A REEL IS ACCEPTABLE BUT MORE THAN 3 RUNNING POCKETS SHORTAGE IS NOT ALLOWED.

5. STRIPPING STRENGTH OF COVER TAPE IS BETWEEN 10 gf TO 70 gf AND STRIPPING ANGLE SHOULD BE WITHIN $165^\circ \sim 180^\circ$.

6. THE PRODUCT IN THE POCKET OF CARRIER TAPE SHOULD BE PLACED IN A SPECIFIED CORRECT POSITION.

7. TAPE AND REEL PER EIA-481

8. DIMENSIONS :



SYN	DESCRIPTION	DATE	APPROVED	APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	MODEL NO.
				Dennis Hung 2012.05.07			Jane Shen 2012.05.07	NTC316-AC1T-A160T
								PAGINATE. 1/1
								SPEC NO. P-672