





RoHS Compliant



REVISIONS							
Rev	DESCRIPTION	DATE	DRAWER	REV	DESCRIPTION	DATE	DRAWER
A	Initial Drawing	2009.01.19	Jamie Li	C			
B				D			
SPECIFICATIONS							
RATING	DC12V 50mA			TIMING			
CONTACT RESISTANCE	500mΩ MAX.			OPERATION (TORQUE)	160±50 gf		
INSULATION RESISTANCE	DC500V - 100MΩ MIN.			STROKE (ANGLE)	0.2±0.1mm		
WITHSTAND VOLTAGE	AC250V-1 MINUTE			CONTACT RESISTANCE	1Ω MAX.		
REMARKS:				(AFTER 100,000 CYCLES LIFE TEST)			




HATCHED AREA SHOWS SOLDERING LAND
(TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.1)

TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.2			SIGNATURES		DATE	MODEL
			DRAWN	CHECKED		
Ø	UNIT mm	SCALE 10/1	Jamie Li	Catherine Lee	2009.01.19	TITLE TACT SWITCH NO. NTC325-AA1J-A160T
REVIEWED	Ken Lin	2009.01.20	APPROVALS	Fred Chen	2009.01.20	

TAIWAN MISAKI ELECTRONICS CO., LTD.

RoHS Compliant



NO.	PART NAME	Q'TY	MATERIAL		SPECIFICATION		
6	TAPE	1	POLYIMIDE				
5	CONTACT PLATE	1	STAINLESS STEEL PLATE		Ag-CLAD		
4	TERMINAL	3	COPPER ALLOY		Ag PLATING OVER Ni PLATING		
3	FRAME	1	LIQUID CRYSTAL POLYMER		BLACK COLOR		
2	STEM	1	LIQUID CRYSTAL POLYMER		WHITE COLOR		
1	COVER	1	STAINLESS STEEL PLATE		Ag PLATING OVER Ni PLATING		
SYM	DESCRIPTION	DATE	APPROVED	SIGNATURES	DATE	M O D E L	
				DRAWN Jamie Li	2010.05.04	TITLE	TACT SWITCH
				CHK'D			
				REV'D		NO.	NTC325-AA1J-A160T
				APP'D James Hung	2010.05.04		
	TAIWAN MISAKI ELECTRONICS CO.,LTD.				DWG NO.	TC325-01	

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliance

Model: NTC325 SERIES

1. Test condition:

Standard test conditions shall be 5~35°C in temperature, 45~85%RH in humidity and 86~106Kpa in atmospheric pressure. Should any doubt arise in judgment, tests shall be conducted at 20±2°C in temperature, 60~70% RH in Humidity and 86~106 kpa in atmospheric pressure.

2. Operating temperature range: -40 ~ +85°C

Preservative temperature range: Single condition: -40 ~ +85°C ; Taping condition: -20 ~ +60°C


3. Construction:

3.1 Shape and dimension are subject to attached drawing regulation.

3.2 Appearance: Whole should be a good completion, no rust, no crack and good plating.

4. Rating: 12V D.C. , 50mA.

5. Electrical Performance:




No.	Items	Test conditions	Specifications
5.1	Contact Resistance	Shall be measure at 1kHz±200Hz (MAX. 20mV, MAX. 50mA.) or 1 A, 5V D.C. By voltage drop method.	500mΩ Max.
5.2	Insulation Resistance	Shall be measured by applying 500V D.C. Between all terminals and between the terminals and the frame for 1 minute ± 5 seconds.	100MΩ Min.
5.3	Withstand Voltage	250V A.C. (50~60Hz 2mA) shall be applied between all terminals and between the terminals and the frame for 1 minute.	No dielectric breakdown shall be occurred.
5.4	Bounce	<p>Lightly striking the center of the stem at a rate encountered in normal use (3 to 4 operations per sec.)</p> 	<p>ON: 10m sec Max. OFF:10m sec Max.</p>

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
			<i>Fred Chen</i> 2009-08-06	<i>Ken Lin</i> 2009.08.06	Max Chen 2009.08.05	Jamie Li 2009.08.05	SE-TC52N
A	NEW RELEASE						PAGINATE
SYM	DISCRIPTION	DATE					1/3

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliance

6. Mechanical Performance:

No.	Items	Test conditions	Specifications
6.1	Operating Force	Placing the switch such that the direction of switch operation is vertical and then gradually increasing the load applied to the center of the stem, the maximum load required for the switch to come to a stop shall be measured. 	160 ± 50 gf.
6.2	Travel	Placing the switch such that the direction of switch operation is vertical and then applying a below static load to the center of the stem, the travel distance for the switch to come to a stop shall be measured. 	0.2 ± 0.1 mm.
6.3	Control Strength	The static load of <u>2kgf</u> shall be applied on top of the terminal in every direction for 15 seconds in any direction on condition of once for one terminal.	Shall be free from extreme wobble, vent or electrical and mechanical abnormality. Not deformation of the appearance.
6.4	Solderability	Soldering temperature: 235±5°C. Soldering time: 2±0.5 seconds.	75% or more of surface area of the portion immersed in solder shall be satisfied.
6.4	Solder Heat Resistance	(1) Manual soldering temperature: Temperature: 350°C Max. Time: 3 Sec. Max. (2) Reflow Soldering: Number of reflow pass: 2 cycles. 	Shall be free from pronounced deforming in appearance. Of item 5.1~5.4 shall be satisfied. Of item 6.1~6.2 shall be satisfied.

		APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
		<i>Fred Chen</i>	Ken Lin 2009.08.06	Max Chen 2009.08.05	Jamie Li 2009.08.05	SE-TC52N
A	NEW RELEASE					PAGINATE
SYM	DISCRIPTION	DATE				2/3

SPECIFICATIONS FOR TACT SWITCH

RoHS Compliance

7. Weather Performance:

No.	Items	Test conditions	Specifications												
7.1	Humidity Test	(1) Temperature: $60\pm2^{\circ}\text{C}$. (2) Relative humidity: 90~95% (3) Duration of test: 500 Hour. (4) Take off a drop water. (5) Standard conditions after test: 1 Hour.	Contact resistance: 500mΩ Max Of item 5.2~5.4 shall be satisfied. Of item 6.1~6.2 shall be satisfied.												
7.2	Heat Test	(1) Temperature: $85\pm2^{\circ}\text{C}$. (2) Duration of test: 500 Hour. (3) Standard conditions after test: 1 Hour.													
7.3	Cold Test	(1) Temperature: $-40\pm2^{\circ}\text{C}$. (2) Duration of test: 500 Hour. (3) Take off a drop water. (4) Standard conditions after test: 1 Hour.													
7.4	Temperature cycle	(1) Test cycle: <u>20</u> cycles. (2) Standard conditions after test: 1 Hour.	<table border="1"> <thead> <tr> <th></th> <th>Temperature</th> <th>Duration of test</th> </tr> </thead> <tbody> <tr> <td rowspan="4">1 cycles</td> <td>$20\pm5^{\circ}\text{C}$</td> <td>1 Hour</td> </tr> <tr> <td>$-40\pm2^{\circ}\text{C}$</td> <td>1 Hour</td> </tr> <tr> <td>$20\pm5^{\circ}\text{C}$</td> <td>1 Hour</td> </tr> <tr> <td>$85\pm2^{\circ}\text{C}$</td> <td>1 Hour</td> </tr> </tbody> </table>		Temperature	Duration of test	1 cycles	$20\pm5^{\circ}\text{C}$	1 Hour	$-40\pm2^{\circ}\text{C}$	1 Hour	$20\pm5^{\circ}\text{C}$	1 Hour	$85\pm2^{\circ}\text{C}$	1 Hour
	Temperature	Duration of test													
1 cycles	$20\pm5^{\circ}\text{C}$	1 Hour													
	$-40\pm2^{\circ}\text{C}$	1 Hour													
	$20\pm5^{\circ}\text{C}$	1 Hour													
	$85\pm2^{\circ}\text{C}$	1 Hour													

8. Durability:


No.	Items	Test conditions	Specifications
8.1	Life Test (Without Load)	(1) Operating speed:120 cycles/minute. (2) Push force: Maximum value of operation force. (3) Operation number: 100,000 times.	Contact Resistance: 1Ω MAX. Operating Force: Within $\pm30\%$ of specifications. Of item 5.2 shall be satisfied. Of item 6.2 shall be satisfied.

			APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	SPEC NO.
			<i>Fred Chen</i>	Ken Lin 2009.08.06	Max Chen 2009.08.05	Jamie Li 2009.08.05	SE-TC52N
A	NEW RELEASE		2009-08-06				PAGINATE
SYM	DISCRIPTION	DATE					3/3

THE PACKING SPECIFICATIONS

RoHS Compliant

1. STRUCTURE AND MATERIALS



NO.	PARTS NAME	MATERIALS
(3)	COVER TAPE	POLYESTER
(2)	CARRIER TAPE	POLYSTYRENE
(1)	REEL	POLYSTYRENE

2. PACKAGING QUANTITY : 1,900 PCS/REEL * 3 REEL/BOX = 5,700 PCS/BOX


3. MORE THAN 10 EMPTY POCKETS SHOULD BE REMAINED AT BOTH ENDS OF THE CARRIER TAPE FOR EACH REEL.

4. SHORTAGE LESS THAN 10 PCS A REEL IS ACCEPTABLE BUT MORE THAN 3 RUNNING POCKETS SHORTAGE IS NOT ALLOWED.

5. STRIPPING STRENGTH OF COVER TAPE IS BETWEEN 10 gf TO 130 gf AND STRIPPING ANGLE SHOULD BE WITHIN 165° ~ 180°.

6. THE PRODUCT IN THE POCKET OF CARRIER TAPE SHOULD BE PLACED IN A SPECIFIED CORRECT POSITION.

7. DIMENSIONS :



SYM	DESCRIPTION	DATE	APPROVED	APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	MODEL NO.
				Fred Chen 0506 2008	Ken Lin 2008.05.05	Max Chen 2008.05.05	Jamie Li 2008.05.05	NTC325-AA1J-A160T
								PAGINATE. 1/1
								SPEC NO. P-455