




Features ➤ 100% EAS Guaranteed ➤ Super Low Gate Charge ➤ Green Device Available ➤ Excellent CdV/dt effect decline ➤ Advanced high cell density Trench technology	Bvdss	Rdson	ID
	30V	3.2mΩ	95A
	Application ➤ PWM applications ➤ Load Switch ➤ Power management		



Package
  
Marking and pin assignment TO252-3L top view Schematic diagram

Package Marking and Ordering Information

Device Marking	Device	Device Package	Quantity
3095K	3095K	TO252-3L	2500

Absolute Maximum Ratings (T_C=25°C unless otherwise specified)

Parameter		Symbol	Value	Unit
Drain-Source Voltage		V _{DS}	30	V
Gate-Source Voltage		V _{GS}	±20	V
Continuous Drain Current, V _{GS} @10V	T _C = 25°C	I _D	95	A
	T _C =100°C		50	A
Pulsed Drain Current ¹		I _{DM}	375	A
Single Pulsed Avalanche Energy ⁴		EAS	100	mJ
Avalanche Current		I _{AS}	-	A
Total Power Dissipation	T _C = 25°C	P _D	50	W
Storage Temperature Range		T _{STG}	-55 ~ 150	°C
Operating Junction Temperature Range		T _J	-55 ~ 150	°C



Thermal Resistance Ratings

Parameter	Symbol	Value	Unit
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	29	$^{\circ}\text{C/W}$
Thermal Resistance Junction to Case	$R_{\theta JC}$	2.5	$^{\circ}\text{C/W}$

Ordering Information

Ordering Number	Package	Pin Assignment			Packing
Halogen Free		G	D	S	
HL3095K	TO252-3L	1	2	3	Tape Reel

Electrical Characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	30	-	-	V
Drain to Source Leakage Current	I_{DSS}	$V_{DS}=30V, V_{GS}=0V$	-	-	1	μA
Gate to Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}, I_D=250\mu A$	1	1.3	1.6	V
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=30A$	-	3.2	3.8	m Ω
		$V_{GS}=4.5V, I_D=20A$	-	4.3	5	
Gate Resistance	R_g	$V_{DS}=0V, V_{GS}=0V, f=1\text{MHz}$	-	1.4	-	Ω
Total Gate Charge(10V) ^{2,3}	Q_g	$V_{DS}=15V, V_{GS}=10V,$ $I_D=30A$	-	35	-	nC
Gate-Source Charge	Q_{gs}		-	6.6	-	
Gate-Drain(“Miller”) Charge	Q_{gd}		-	7	-	
Turn-On Delay Time ^{2,3}	$t_{d(on)}$	$V_{DD}=15V, V_{GS}=10V,$ $R_G=3\Omega, I_D=30A$	-	8	-	ns
Rise Time	t_r		-	15	-	
Turn-Off Delay Time	$t_{d(off)}$		-	33	-	
Fall Time	t_f		-	10	-	
Input Capacitance	C_{iss}	$V_{DS}=15V, V_{GS}=0V, f=1\text{MHz}$	-	2200	-	pF
Output Capacitance	C_{oss}		-	239	-	
Reverse Transfer Capacitance	C_{rss}		-	201	-	
Continuous Source Current	I_S	$V_G=V_D=0V, \text{Force Current}$	-	95	-	A
Pulsed Source Current	I_{SM}		-	375	-	A



Diode Forward Voltage	V_{SD}	$V_{GS}=0V, I_S=30A, T_J=25^{\circ}C$	-	-	1.1	V
-----------------------	----------	---------------------------------------	---	---	-----	---

Note :

1. Repetitive Rating: Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed, pulse width=300us, duty cycle=2%.
3. Essentially independent of operating temperature.
4. The EAS data shows Max. rating. The test condition is $V_{DD}=15V, V_{GS}=10V, L=0.5mH$.

Typical Performance Characteristics

Fig1 Output Characteristics




Fig2 Typical Transfer Characteristics




Fig3 On-resistance vs. Drain Current




Fig4 Gate Charge Waveform




Fig5 Capacitance Characteristics




Fig6 Normalized Breakdown Voltage vs. Tj




Fig7 Normalized Transient Impedance




Fig8 Maximum Safe Operation Area




Fig9 Switching Time Waveform






Fig10 EAS Waveform



Package Mechanical Data TO252-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.380	0.087	0.094
A1	0.000	0.100	0.000	0.004
B	0.800	1.400	0.031	0.055
b	0.710	0.810	0.028	0.032
C	0.460	0.560	0.018	0.022
C1	0.460	0.560	0.018	0.022
D	6.500	6.700	0.256	0.264
D1	5.130	5.460	0.202	0.215
E	6.000	6.200	0.236	0.244
e	2.286TYP		0.090TYP	
e1	4.327	4.727	0.170	0.186
M	1.778REF		0.070REF	
N	0.762REF		0.018REF	
L	9.800	10.400	0.386	0.409
L1	2.9REF		0.114REF	
L2	1.400	1.700	0.055	0.067
V	4.830REF		0.190REF	
Φ	1.100	1.300	0.043	0.051



Important Notice and Disclaimer

HL Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice.

Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

HL Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does HL Microelectronics assume any liability for application assistance or customer product design.

HL Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of HL Microelectronics.

HL Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of HL Microelectronics.