

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_BMA-50-2-2/119_N

Rev.: F



Description

Straight panel cable jack, flange mount

Interface Standards
IEC 60169-33_MIL-STD-348A/321

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact plugged
Outer contact soldered
Weight 0.0055 kg

Environmental Data

Operating Temperature -65 °C to 125 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Other body part	Stainless Steel	
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing DCA-00008815
Assembly instruction DOC-0000180997
Mounting hole DOU-00008816

Ordering Information

Single package 25_BMA-50-2-2/119_NE
Bulk 100 pcs package 25_BMA-50-2-2/119_NH

Additional Information

Suitable cable EZ_86_TP_M17

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions