KAMAYA OHM

No.:	RGC-K-HTS-0001 /13
Date:	2017. 4. 21

Data sheet

Title: FIXED THICK FILM CHIP RESISTORS; RECTANGULAR TYPE & PRECISION

Style: RGC1/32,1/20,1/16S,1/16,1/10,1/8

AEC-Q200 qualified (Without RGC1/32)

RoHS COMPLIANCE ITEM
Halogen and Antimony Free

Note: ・Stock conditions
Temperature: +5°C ~ +35°C
Relative humidity: 25% ~ 75%
The period of guarantee: Within 2 year from shipmen t by the company.
Solderability shall be satisfied.
・Product specification contained in this data sheet
are subject to change at any time without notice.
・If you have any questions or a Purchasing Specification for any quality
Agreement is necessary, please contact our sales staff.

釜屋電機株式會社
KAMAYA ELECTRIC CO., LTD.
Hokkaido Research Center
Approval by: T. Sannomiya
Drawing by: M. Shibuya

1. Scope

1.1 This data sheet covers the detail requirements for fixed thick film chip resistors; rectangular type & precision, style of RGC1/32,1/20,1/16S,1/16,1/10,1/8.

1.2 Applicable documents

JIS C 5201–1: 2011, JIS C 5201–8: 2014, JIS C 5201–8–1: 2014
IEC60115–1: 2008, IEC60115–8: 2009, IEC60115–8–1: 2014
EIAJ RC–2134C–2010

2. Classification

Type designation shall be the following form.

(Example)

RGC	1/8	C	123	D	TP
1	2	3	4	5	6
Style					

1 Fixed thick film chip resistors; rectangular type & precision — Style
2 Rated dissipation and / or dimension
3 Temperature coefficient of resistance

K	$\pm 100 \times 10^{-6}$/ °C
C	$\pm 50 \times 10^{-6}$/ °C

4 Rated resistance

123	E24 Series, 3 digit, Ex. 123--> 12kΩ,
1000	E96 Series, 4 digit, Ex. 1000-->100Ω 1022--> 10.2kΩ

5 Tolerance on rated resistance

B	±0.1%
D	±0.5%
F	±1%

6 Packaging form

B	Bulk (loose package)
PA	Press pocket taping
TH	Paper taping
TP	

3. Rating

3.1 The ratings shall be in accordance with Table–1.

Table–1

Style	Rated dissipation (W)	Temperature coefficient of resistance (10^{-6} / °C)		Rated resistance range(Ω)	Preferred number series for resistors	Tolerance on rated resistance
RGC1/32	0.03	C	± 50	100~100k	E24,96	D(±0.5%)
RGC1/20	0.05	C	± 50	1k~1M	E24,96	B(±0.1%), D(±0.5%)
		K	±100	51~976		
RGC1/16S	0.063	C	± 50	100~1M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
		K	±100	1.02M~3.3M		
				10~97.6		
RGC1/16	0.1	C	± 50	100~1M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
		K	±100	1.02M~3.3M		
				10~97.6		
				3.3~9.76		D(±0.5%)F(±1%)
RGC1/10	0.125	C	± 50	10~3.3M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
				3.3~9.76		D(±0.5%)F(±1%)
RGC1/8	0.25	C	± 50	10~4.7M	E24,96	B(±0.1%), D(±0.5%) F(±1%)
				3.3~9.76		F(±1%)

Style	Limiting element voltage (V)	Isolation voltage (V)	Category temperature range(°C)
RGC1/32	15	50	–55~+125
RGC1/20	25		–55~+155
RGC1/16S	50	100	
RGC1/16			
RGC1/10	150		
RGC1/8	200		

3.2 Climatic category

3.2.1 RGC1/32

55/125/56

Lower category temperature	– 55 °C
Upper category temperature	+125 °C
Duration of the damp heat, steady state test	56days

3.2.2 RGC1/20,1/16S,1/16,1/10,1/8

55/155/56

Lower category temperature	– 55 °C
Upper category temperature	+155 °C
Duration of the damp heat, steady state test	56days

3.3 Stability class


5%

Limits for change of resistance:

– for long - term tests	±(5%+0.1Ω)
– for short - term tests	±(1%+0.05Ω)

3.4 Derating

The derated values of dissipation at temperature in excess of 70 °C shall be as indicated by the following curve.



Figure–1 Derating curve

3.5 Rated voltage

d.c.or a.c.r.m.s.voltage calculated from the square root of the product of the rated resistance and the rated dissipation.

$$E = \sqrt{P \cdot R}$$

E: Rated voltage (V)
P: Rated dissipation (W)
R: Rated resistance (Ω)

Limiting element voltage can only be applied to resistors when the resistance value is equal to or higher than the critical resistance value.

At high value of resistance, the rated voltage may not be applicable.

4. Packaging form


The standard packaging form shall be in accordance with Table–2.

Table–2

Symbol	Packaging form		Standard packaging quantity / units	Application
B	Bulk (loose package)		1,000 pcs.	RGC1/32,1/20,1/16S,1/16,1/10,1/8
PA	Press pocket taping (paper taping)	8mm width, 2mm pitches	20,000 pcs.	RGC1/32
			15,000 pcs.	RGC1/20
TH	Paper taping	8mm width, 2mm pitches	10,000 pcs.	RGC1/16S
TP	Paper taping	8mm width, 4mm pitches	5,000 pcs.	RGC1/16, 1/10, 1/8

5. Dimensions

5.1 The resistor shall be of the design and physical dimensions in accordance with Figure–2 and Table–3.



Figure–2

Table–3 Unit: mm

Style	L	W	H	c	d
RGC1/32	0.4±0.02	0.2±0.02	0.13±0.02	0.08±0.03	0.1±0 .03
RGC1/20	0.6±0.03	0.3±0.03	0.23±0.03	0.1±0.05	0.15±0 .05
RGC1/16S	1.0±0.05	0.5±0.05	0.35±0.05	0.2±0.1	$0.25^{+0.05}_{-0.10}$
RGC1/16	1.6±0.1	$0.8^{+0.15}_{-0.05}$	0.45±0.10	0.25±0.10	0.3±0.1
RGC1/10	2.0±0.1	1.25±0.10	0.6±0.1	0.4±0.2	0.4±0.2
RGC1/8	3.1±0.1	1.6±0.15	0.6±0.1	0.5±0.25	0.5±0.25

5.2 Net weight (Reference)

Style	Net weight(mg)
RGC1/32	0.035
RGC1/20	0.16
RGC1/16S	0.6
RGC1/16	2
RGC1/10	5
RGC1/8	9

6. Marking

The Rated resistance shall be marked in 3 digits (E24) or 4 digits (E96) and marked on over coat side.


- E24 series: 3 digits, E96 series: 4 digits

  In case of the resistance value that E96 overlaps with E24, It is marked by either.

The Rated resistance of RGC1/16 should not be marked in 4 digits.

The Rated resistance of RGC1/32,1/20,1/16S should not be marked.


Marking example	Contents	Application
123	12×10^{3} [Ω] → 12 [kΩ]	RGC1/16,1/10,1/8
3R3	3. 3 [Ω]	Less than 10Ω of RGC1/16,1/10,1/8
5623	562×10^{3} [Ω] → 562[kΩ]	RGC1/10,1/8
12R7	12.7 [Ω]	RGC1/10,1/8




Unit: mm
:Copper clad
:Solder resist

Style	a	b	c	d
RGC1/20	0.3	1.1	0.45	2.15
RGC1/16S	0.6	1.9	0.7	2.0
RGC1/16	1.0	3.6	1.2	3.0
RGC1/10	1.2	4.0	1.65	3.0
RGC1/8	2.5	5.0	2.0	2.5

RGC BOUND STRENGTH OF THE END FACE PLATING TEST SUBSTRATE



Unit: mm
:Copper clad
:Solder resist




RGC1/32 BOUND STRENGTH OF THE END FACE PLATING TEST SUBSTRATE


Figure–4

Remark 1). Material: Epoxide woven glass
Thickness: 1.6mm Thickness of copper clad: 0.035mm

• RGC1/16S,1/16,1/10,1/8



•RGC1/32,1/20



Figure–5

9. Taping


9.1 Applicable documents JIS C 0806–3: 2014, EIAJ ET–7200C: 2010

9.2 Taping dimensions

9.2.1 Press pocket taping (Paper taping, 8mm width, 2mm pitches)

Taping dimensions shall be in accordance with Figure–6 and Table–5.

Unit: mm



Figure–6


Table–5 Unit: mm

Style	A	B	t_1	t_2	t_3
RGC1/32	0.24±0.03	0.45±0.03	0.31±0.03	0.36±0.03	0.15±0.02
RGC1/20	0.37±0.05	0.67±0.05	0.42±0.03	0.45±0.05	0.27±0.02

9.2.2 Paper taping (8mm width, 2mm pitches)

Taping dimensions shall be in accordance with Figure–7 and Table–6.

Unit: mm



Figure–7


Table–6 Unit: mm

Style	A	B	t_1	t_2
RGC1/16S	$0.65^{+0.05}_{-0.10}$	$1.15^{+0.05}_{-0.10}$	0.4 ± 0.05	0.5max.

9.2.3 Paper taping (8mm width, 4mm pitches)

Taping dimensions shall be in accordance with Figure–8 and Table–7.

Unit: mm




Figure–8


Table–7 Unit: mm

Style	A	B	t_1	t_2
RGC1/16	1.15 ± 0.15	1.9 ± 0.2	0.6 ± 0.1	0.8max.
RGC1/10	1.65 ± 0.15	2.5 ± 0.2	0.8 ± 0.1	1.0max.
RGC1/8	2.00 ± 0.15	3.6 ± 0.2		

1). The cover tapes shall not cover the sprocket holes.
2). Tapes in adjacent layers shall not stick together in the packing.
3). Components shall not stick to the carrier tape or to the cover tape.
4). Pitch tolerance over any 10 pitches ±0.2mm.
5). The peel strength of the top cover tape shall be with in 0.1N to 0.5N on the test method as shown in the following RGC1/32,1/20: Figure–9, RGC1/16S, 1/16, 1/10, 1/8: Figure–10.
6). When the tape is bent with the minimum radius for 25 mm, the tape shall not be damaged and the components shall maintain their position and orientation in the tape.
7). In no case shall there be two or more consecutive components missing.
The maximum number of missing components shall be one or 0.1%, whichever is greater.
8). The resistors shall be faced to upward at the over coating side in the carrier cavity.



Figure–9




Figure–10

9.3 Reel dimension

Reel dimensions shall be in accordance with the following Figure–11 and Table–8.

Plastic reel (Based on EIAJ ET–7200C) Unit: mm



Figure–11


Table–8 Unit: mm

Style	A	B	Note
RGC1/32,1/20,1/16S,1/16,1/10,1/8	9 +1.0 0	11.4±1.0	Injection molding
		13±1.0	Vacuum forming

Note: Marking label shall be marked on a place of Marking A or two place of marking A and B.

9.4 Leader and trailer tape.

(Example)



Figure–12

10. Marking on package

The label of a minimum package shall be legibly marked with follows.

10.1 Marking A

(1) Classification

(Style, Temperature coefficient of resistance, Rated resistance, Tolerance on rated resistance, Packaging form)

(2) Quantity (3) Lot number (4) Manufacturer's name or trade mark (5) Others

10.2 Marking B (KAMAYA control label)