



D

C

B

A



ACT 26 X X XX X X

KEYING POSITION

CONTACT CODE

P = 500 CYCLE PIN

S = 500 CYCLE SOCKET

A = LESS PIN

B = LESS SOCKET

H = 1500 CYCLE PIN

J = 1500 CYCLE SOCKET

INSERT ARRANGEMENT

SHELL SIZE

FINISH

J = OLIVE DRAB CADMIUM

M = NICKEL

STRAIGHT PLUG

GENERAL IDENTIFIER

ACT = ALL COMPOSITE TECHNOLOGY

5. FOUR FLATS FOR SHELL SIZES A - E.
EIGHT FLATS FOR SHELL SIZES F - J.
4. FOR APPLICABLE KEYING DIAGRAM, SEE MIL-DTL-38999.
FOR INSERT ARRANGEMENTS, SEE MIL-STD-1560. CONSULT
FACTORY FOR AVAILABILITY.
3. GENERAL SPECIFICATIONS: THIS CONNECTOR MEETS THE
INTERMATEABILITY REQUIREMENTS OF MIL-DTL-38999 SERIES III.
2. MATERIAL/FINISH
- SHELL - COMPOSITE, PLATED.
- COUPLING RING - COMPOSITE, UNPLATED.
- CONTACTS - COPPER ALLOY, DEUTSCHCOAT V (H/J) OR GOLD (P/S).
- RESILIENT INSERTS - SILICONE ELASTOMER.
- PLASTIC INSERTS - THERMOPLASTIC.

1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
THREAD CALLOUT IS METRIC.

PART NUMBER	SHELL SIZE	Ø A MAX.	B THREAD
ACT26xAxxxx	09	.858	M12x1.0-6g 0.100R
ACT26xBxxxx	11	.984	M15x1.0-6g 0.100R
ACT26xCxxxx	13	1.157	M18x1.0-6g 0.100R
ACT26xDxxxx	15	1.280	M22x1.0-6g 0.100R
ACT26xExxxx	17	1.406	M25x1.0-6g 0.100R
ACT26xFxxxx	19	1.516	M28x1.0-6g 0.100R
ACT26xGxxxx	21	1.642	M31x1.0-6g 0.100R
ACT26xHxxxx	23	1.768	M34x1.0-6g 0.100R
ACT26xJxxxx	25	1.890	M37x1.0-6g 0.100R

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
CRAIG BROWN
CHK
EHAB ALAWNEH
APVD
-
PRODUCT SPEC
-
APPLICATION SPEC
-
WEIGHT
-
CUSTOMER DRAWING

150102

150102

-

NAME

ACT SERIES
PLUG ENVELOPE

SIZE

A2

CAGE CODE

-

DRAWING NO

©-ACT26xxxxxx

RESTRICTED TO

-

SCALE

3.000

SHEET

1

OF

1

REV

A

TE Connectivity

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[YACT26MF35SD000000](#)