

	0	1	2	3	4	5	6	7	8	9	10	11
A								REV.	EC#	DESCRIPTION	DATE	DRAWN
B								1.00		初版发行	2020-8-18	CHECK
C												APPROVED
D												
E												
F												
G												
H												

孔位
A B

2	7.5	2.5
3	10	5.0
4	12.5	7.5
5	15.0	10.0
6	17.5	12.5
7	20.0	15.0
8	22.5	17.5
9	25.0	20.0
10	27.5	22.5
11	30.0	25.0
12	32.5	27.5
13	35.0	30.0
14	37.5	32.5
15	40.0	35.0

适应基板厚度: 1.2mm~1.6mm

温度范围: -25°C~85°C

额定电压: 250V AC/DC

额定电流: 3A

接触电阻: ≤0.02 Ω

绝缘电阻: ≥1000MΩ

耐压: 1000V AC/minute

技术要求:

- 1) 材质: 见附表;
- 2) 电镀: 见附表;
- 3) 塑件表面平整、光洁、无毛刺、气泡、烧焦、变形、浇口无拉伤、多料或缺料等不良现象;
- 4) 端子表面无氧化、电镀不良等现象。

2	PIN	N PCS	材质: 黄铜, 电镀: 镀亮锡60u"MIN		
1	Housing	1 PCS	材质: PA66 (UL94V-0), 颜色: 本色		
NO.	NAME	Q'TY	DESCRIPTION		

深圳市韩下电子有限公司

DRAW :	黄彬	2020-8-18	TITLE:	针座			
DESIGN:			SERIES: 1501 SERIES			DRAW NAME: HX-5264-3A	
CHECK:	张伟	2020-8-18					
APPROVED	罗小春	2020-8-18	P/N:			DRAW NO.	
CUSTOMER DRAWING						UNIT: mm	SHEET: 1/1
REV. 1.00						N/A	

GENERAL TOLERANCES

DIM	TOL	DIM	DEG
X.	X°		±3.00°
X.X	±0.35	X.X°	±2.00°
X.XX	±0.25	X.XX°	±1.00°
X.XXX	±0.15	X.XXX°	