

MGR[®]

GJ-5FA-L

直流固态继电器 PCB 安装系列


DC solid state relays PCB installation series



◎ 产品概述 Product overview

- ◆ 额定电流: 3A, 5Amps
- ◆ 额定电压: 5-220VDC
- ◆ 控制电压: 3-32VDC
- ◆ 控制电流: $\leq 10\text{mA}$
- ◆ "超低" 的输入电流
- ◆ 低输出断态泄漏电流
- ◆ 低输出通态压降
- ◆ 低阻抗 MOSFET 输出, 最大限度减少总功耗
- ◆ 金属壳体散热效果显著
- ◆ 标准的英规 PCB 安装尺寸
- ◆ Rated current: 3A, 5Amps
- ◆ Rated voltage: 5-220VDC
- ◆ Control voltage: 3-32VDC
- ◆ Control current: $\leq 10\text{mA}$
- ◆ "Ultra low" input current
- ◆ Low output off-leakage current
- ◆ Low output on-State voltage drop
- ◆ Low impedance MOSFET output, minimizing total power
- ◆ Metal shell cooling effect
- ◆ Standard UK standard PCB mounting dimensions

◎ 型号含义 Type meaning



- ① 3A, 5A
- ② 直流控直流 Direct current control
- ③ 单排 Single row

说明: 常用于空调机, 捆钞机及其它家用电器

Description: commonly used in air conditioners, banknote and other household appliances

◎ 安装尺寸及接线图 Installation dimensions and wiring diagram

