

Features

- Uses advanced SGT technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent gate charge x $R_{DS(on)}$ product(FOM)

Application


- Motor control and drive
- Battery management
- DC/DC

Product Summary



Package	TOLL
V_{DS}	90V
$R_{DS(on)}@V_{GS}=10V$	2.25mΩ
I_D	226A

Package Marking

TOLL Top View



TOLL Bottom View



Type	Package	Marking	Reel Size	Tape Width	Packing	Qty
LR026N09XD10	TOLL	LR026N09XD10	330*28.5mm	24mm	Reel&Tape	2000

Maximum Ratings (TC=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	90	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous drain current $T_c=25^{\circ}C$ (Silicon limit) $T_c=100^{\circ}C$ (Silicon limit)	I_D	226 143	A
Pulsed Drain Current	I_{DM}	840	A
Maximum Power Dissipation	P_d	250	W
Single pulse avalanche energy	E_{AS}	812	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	°C

Thermal Characteristic

Thermal Resistance,Junction-to-Case	R_{thJC}	0.5	°C/W
-------------------------------------	------------	-----	------

Electrical Characteristics (T_C=25°C unless otherwise noted)

Parameter	Symbol	Condition	min	typ	max	Unit
-----------	--------	-----------	-----	-----	-----	------

Static Characteristic

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	90	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0	3.0	4.0	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=80V, V_{GS}=0V$	-	-	1	μA
Gate-source leakage current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	±100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$I_D=30A, V_{GS}=10V$	-	2.25	2.6	mΩ

Dynamic Characteristic

Input Capacitance	C_{iss}	$V_{DS}=40V, V_{GS}=0V,$ $f=1MHz$	-	4955	-	pF
Output Capacitance	C_{oss}		-	2087	-	
Reverse Transfer Capacitance	C_{rss}		-	82	-	
Gate resistance	R_g	$f=1MHz$	-	0.9	-	Ω
Gate Total Charge	Q_G	$V_{DS}=40V, I_D=65A,$ $V_{GS}=10V$	-	64	-	nC
Gate-Source charge	Q_{gs}		-	23	-	
Gate-Drain charge	Q_{gd}		-	10	-	
Turn-on delay time	$t_{d(on)}$	$V_{GS}=10V, V_{DS}=40V,$ $R_G=3\Omega$	-	21	-	ns
Rise time	t_r		-	13	-	
Turn-off delay time	$t_{d(off)}$		-	48	-	
Fall time	t_f		-	12	-	

Body Diode Characteristic

Diode Forward Voltage	V_{SD}	$V_{GS}=0V, I_{SD}=125A$	-	0.8	1.2	v
Reverse Recovery Time	t_{rr}	$I_F = 125A$ $di/dt = 100A/\mu s$	-	80	-	ns
Reverse Recovery Charge	Q_{rr}		-	147	-	nC

Typical Performance Characteristics




Figure 1 Output Characteristics




Figure 4 Rdson-Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 Rdson- Drain Current




Figure 6 Source- Drain Diode Forward




Figure 7 Capacitance vs Vds




Figure 9 Power De-rating




Figure 8 Safe Operation Area




Figure 10 Current De-rating








Figure 11 Normalized Maximum Transient Thermal Impedance

Test Circuit & Waveform



Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Package Outline:TOLL



Revision History:

Revision	Date	Major changes
1.0	2025/7/15	Release of Preliminary version.
2.0	2025/10/16	Update Qg Qgs Qgd.
3.0	2025/11/21	Update EAS.
4.0	2025/12/03	The product name has been changed to LR026N09XD10